

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 145 653 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
17.10.2001 Bulletin 2001/42

(51) Int Cl.7: **A23N 5/00**

(21) Application number: **00107856.7**

(22) Date of filing: **12.04.2000**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

• **Ramelan, Emong Emma**
Cipayung Jakarta Timur (ID)
• **Murtiasrini, Retno**
Magelang 56117 (ID)

(71) Applicant: **PT Aneka Messer Industrial Gases**
Kawasan Industri Jababeka II
Cikarang, Bekasi 17550 (ID)

(74) Representative: **Staudt, Armin, Dipl.-Ing.,**
Messer Griesheim GmbH
Fritz-Klatte-Strasse 6
65933 Frankfurt (DE)

(72) Inventors:
• **Jalil, Abdul, d/a H. Abdul Rahman Aly**
Nganjuk, Jawa Timur (ID)

(54) **Method for cracking candle nuts**

(57) It order to provide a method for cracking of candle nuts with a short processing time and resulting in a good quality product at a high yield, it is suggested that the candle nuts (4) are shock frozen in a cooling bath (2) of a liquified cryogenic gas




Fig. 1

EP 1 145 653 A1

Description

[0001] Candle nut ("*Aleurites molluccana*, Wild") is a plant from Malaya. This plant is one of the *Euphobiaceae* family, *Aleurites* genus and has six species that spread in tropic and sub-tropic countries. In Germany candle nut is known as "Belgaum walnut" and in Indonesia it is called "kemiri". This plant has an important economic value and good prospect for daily use. People can use its seeds for spice, the bark for medicine, the oil seeds for soap, paint, cosmetics, industrial batik and the wood for matches.

[0002] Until now there are several traditional ways to crack the shell. For example the nuts are exposed to the sun for 7 days and then the shell is cracked by hitting with an hammer. This method needs a long processing time and the yield of good quality candle nut is only about 40 %.

[0003] In another known method for cracking the shell the candle nuts are fried in sand before milling. However by using this method the candle nut becomes brownish and are not attractive and the usable oil content of the nuts is reduced, so that the yield of the whole candle nut is only about 35 %.

[0004] In a further known method the candle nuts are cracked one by one using a hammer. This method needs much more time and the percentage of the whole yield is only 30 %.

[0005] The traditional methods for removing the shell of candle nuts are not suitable to achieve the quantity and the quality demanded by the market.

[0006] Therefore it is an object of this invention to provide a method for cracking of candle nuts with a short processing time and resulting in a good quality product at a high yield.

[0007] This object is achieved by a method, which is characterised in that the candle nuts are shock frozen in a liquified cryogenic gas.

[0008] A cryogenic gas in this context means liquified gases like nitrogen, oxygen, carbon dioxide, noble gases or air. In the context of this invention "shock freezing" means rapid cooling by using a liquified cryogenic gas.

[0009] By shock freezing the outer shell and inner part of the shell ("inner shell") of the candle nuts becomes a frozen solid and brittle, but the inner part of the candle nuts remain unfrozen so that the shell can be easily removed, so that the damage of the inner part can be avoided. This gives a good quality result and a high yield.

[0010] Furthermore, by the shock freezing mechanical stresses are induced in the outer shell which usually cause it to crack open automatically. Therefore the cracking of the candle nuts needs only a short processing time. The processing time is further reduced since a plurality of nuts can be treated at the same time.

[0011] It is preferred that the candle nuts are held at a first temperature in the range between 0 °C and 50 °C and after that they are rapidly cooled by contact with the

liquified cryogenic gas, having a temperature lower than -180 °C. The first temperature range represents a temperature about ambient temperature. The difference between ambient temperature and a temperature lower than -180 °C is high enough to cause the cracking of the shell and it does not require a lot of work and energy to treat candle nuts having ambient temperature by shock freezing.

[0012] It was found most suitable to provide a cooling bath of the liquified cryogenic gas and to immerse the candle nuts into the bath. Using a cooling bath ensures an effective cooling at reasonable low costs. Furthermore it allows a reproducible treatment of a plurality of candle nuts at the same time.

[0013] It was found most advantageous in this context that a plurality of candle nuts are filled in a porous basket and the basket is immersed into the cooling bath of the liquified cryogenic gas. Using of a basket simplifies the immersing of a plurality of the candle nuts into the bath and the removing out of them from the bath. Furthermore it allows to establish a fixed treating time in the cooling bath. In order to enable an direct contact of the liquified cryogenic gas with the candle nuts, a porous basket is preferred.

[0014] It was found suitable to use liquid nitrogen as liquified cryogenic gas. Liquid nitrogen is easy to handle and not very cost intensive. At atmospheric pressure the boiling point of liquid nitrogen is -196 °C.

[0015] The most preferred treating period during which the candle nuts are in contact with the liquified cryogenic gas is in the range between 10 seconds and 150 seconds. This treating period is sufficient that all or at least most of the shells crack.

[0016] Additional features and advantages of the invention ensue from the description provided below, where an embodiment is explained in more detail by reference to the drawing. In the drawing

Figure 1 shows a schematic presentation of a basket filled with candle nuts, which is immersed into a cooling bath of liquid nitrogen and

Figure 2 shows a schematic view of a cross section of a single candle nut after immersion into the cooling bath.

[0017] In **Figure 1** the designation number 1 indicates a dewar containing a cooling bath 2 of liquid nitrogen having a temperature of -196 °C. A basket 3 made of stainless steel wires is immersed into the cooling bath 2. The basket 3 is filled with candle nuts 4. It can be moved up and down as is indicated by the arrow 5.

[0018] In the following an embodiment of the method according to the invention will be disclosed by reference to **Figure 1**:

Example 1

with the liquified cryogenic gas for a period time between 10 seconds and 150 seconds.

[0019] A half of a kilo of candle nuts 4 having ambient temperature (about 25 °C) is filled into the stainless steel basket 3. The candle nuts 4 are immersed into the cooling bath 2 of liquid nitrogen by moving the basket 3 downwards into the dewar 1. 5

[0020] In the cooling bath 2 the candle nuts 4 are rapidly cooled to a temperature of about -196 °C. Due to this shock freezing mechanical stresses are induced in the outer shell of the candle nuts 4 which cause the shell to crack. 10

[0021] The cooling procedure is stopped after an immersing time of 80 seconds by pulling up the basket 3. The outer shell of nearly all of the candle nuts 4 is cracked; but the inner part of the candle nuts 4 remains unfrozen. 15

[0022] Figure 2 is showing a cross section of a single candle nut after this treatment. The outer shell 6 as well as the thin inner shell 7 are frozen and brittle. The inner part 8 however is unfrozen. The outer shell 6 and the inner shell 7 can be removed easily by means of a milling machine. 20

[0023] The total yield of the candle nuts is 82.3 %. For treating candle nuts according to the method of the invention, the liquid nitrogen consumption is 0.9 kg per kilo candle nuts. 25

Claims

30

1. Method for cracking the shell of candle nuts (4), characterised in that the candle nuts (4) are shock frozen in a liquified cryogenic gas. 35
2. Method according to claim 1, characterised in that the candle nuts (4) are held at a first temperature in the range between 0 °C and 50 °C and after that it is rapidly cooled by contact with the liquified cryogenic gas, having a temperature lower than -180 °C. 40
3. Method according to claim 1 or claim 2, characterised in that a cooling bath (2) of the liquified cryogenic gas is provided and that the candle nuts (4) are immersed into the bath. 45
4. Method according to claim 3, characterised in that the candle nuts (4) are filled in a porous basket (3) and the basket (3) is immersed into the bath (2) of the liquified cryogenic gas. 50
5. Method according to one of the claims 1 to 4, characterised in that the liquified cryogenic gas is liquid nitrogen. 55
6. Method according to one of the claims 1 to 5, characterised in that the candle nuts (4) are in contact




Fig. 1




Fig. 2



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 10 7856

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	FR 2 450 067 A (BERTIN & CIE) 26 September 1980 (1980-09-26) * the whole document *	1-3,5	A23N5/00
A	---	4,6	
X	WO 99 15843 A (BIVINS WILLIAM W JR ; ROVIROSA SALLY STAHMANN (US); STAHMANN WILLIA) 1 April 1999 (1999-04-01) * page 4, line 22 - page 6, line 16; claims 1-16 *	1,2,5,6	
A	---	3,4	
A	US 4 742 686 A (COOK DOUGLAS P) 10 May 1988 (1988-05-10) * the whole document *	1	
A	DE 19 24 901 A (INGENIEURBÜRO JOACHIM G MÖLLER) 19 November 1970 (1970-11-19) * the whole document *	1	
A	DATABASE WPI Section Ch, Week 199629 Derwent Publications Ltd., London, GB; Class D14, AN 1996-285133 XP002147059 & RU 2 048 128 C (CANNING VEGETABLES DRYING IND), 20 November 1995 (1995-11-20) * abstract *	1	<div>TECHNICAL FIELDS SEARCHED (Int.Cl.7)</div> <div>A23N</div>
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 11 September 2000	Examiner Merckx, A
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03/02 (P04-001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 10 7856

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-09-2000

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2450067	A	26-09-1980	NONE	
WO 9915843	A	01-04-1999	AU 9579298 A	12-04-1999
US 4742686	A	10-05-1988	NONE	
DE 1924901	A	19-11-1970	NONE	
RU 2048128	C	20-11-1995	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82